

Model FX-1 Mini Gas deTECtor



FEATURES

- ALL-IN-ONE ELECTRONICS SENSOR PACKAGE
- TWO ALARM LEVELS - WARNING AND DANGER
- FLASHLIGHT TEST, SILENCE, AND RESET OF ALARMS
- AUDIBLE AND VISUAL ALARMS
- CELL FAILURE ALARM
- NEMA 4X FIBERGLASS ENCLOSURE
- MAINTENANCE FREE
- EASY INSTALLATION
- PROVEN ELECTROCHEMICAL SENSOR TECHNOLOGY
- MINI SIZE, ONLY 3 1/2" X 6" X 3 1/2"
- FAST RESPONSE FOR INCREASED SAFETY
- AUXILIARY RELAY
- LONG SENSOR LIFE

DESCRIPTION

The FX-1 is a single gas, wall mounted, continuous gas leak detector for toxic gases or oxygen. Each detector utilizes proven electrochemical sensor technology to detect gas or oxygen in the low parts per million (ppm) or percent (%) of oxygen levels.

During normal operation, a green LED illuminates confirming the unit is functional. Two alarms, Warning and Danger, are provided with each indicating a specific concentration of gas. The warning alarm illuminates the yellow LED, and the Danger alarm illuminates a flashing red LED, sounds the audible alarm, and engages a 10 amp relay for external alarm devices.

Housed in a NEMA 4X fiberglass enclosure, the FX-1 is easy to install and operate. This detector has one special feature that enables its alarms to be tested, silenced and reset remotely by shining a flashlight on the front panel or by manually pressing a button on the side of the unit.

HIGHLIGHTS

Model FX-1 Mini Gas deTECTOR



SPECIFICATIONS

Measuring Principle	Electrochemical sensor
Response Time	Less than 8 seconds to full alarm
Audible Alarm	Pulsating Piezo Buzzer (105 dB)
Auxiliary Relay Contact	Danger - DPST 10A @ 125 VAC - latching
Auxiliary Outputs	Cell failure +12VDC (600 ohms minimum) Warning +12VDC (600 ohms minimum) Power Failure +12VDC (600 ohm minimum)
Drift	Less than 2% per month
Temperature Range	-15° to 40°C (5° to 104°F)
Humidity Range	15-90% (non-condensing)
Power Supply	110VAC, 50/60 Hz Remote Transformer 220VAC, 50 Hz Remote Transformer (opt.) Hard Wire Power Pack 100-240 VAC, 25 Watt (optional)
Enclosure	NEMA 4X Fiberglass
Weight	6 pounds (2.7 kg)
Dimensions	3.6" wide x 6.0" high x 3.5" deep
Warranty	Electronics 2 years, toxic gas sensor 1 year

ALARM POINT	Danger (ppm)		
	Warning (ppm)		
Standard Range (ppm)			
Chlorine	0-10	1.0	3.0
Sulphur Dioxide	0-10	1.0	3.0
Carbon Moxoxide	0-500	35	50
Hydrogen	0-200	35	50
Hydrogen Sulphide	0-10	1.0	3.0
Nitric Oxide	0-10	1.0	3.0
Nitrogen Dioxide	0-10	1.0	3.0
Oxygen	0-25%	19.5%	16%
Ammonia	0-200	35	50
Hydrogen Cyanide	0-10	1.0	3.0
Ozone	0-10	1.0	3.0
Hydrogen Chloride	0-10	1.0	



PO Box 39
2101 Creek Road
Glen Moore, PA
19343
(610) 942-2888
(800) 874-0590
fax: (610) 942-2769
www.foxcroft.com

Distributed By:

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continuous product improvement Foxcroft reserves the right to make product changes without notice. No liability is accepted for any consequential losses, injury or damage resulting from the use of this document or from any omissions or errors herein.